

575XP New!

Our most advanced saw for professional users who require peak performance. Larger displacement, higher peak power and torque and even better ergonomics combine to ensure maximum productivity.



More power where needed most

The X-TORQ engine design increases torque over a wider rpm range and results in maximum cutting power.



Improved handle design

The rear handle is asymmetrically designed with comfort inserts for a more solid and less tiring grip.



Optimized saw body

No protruding parts, a smooth underside, rounded starter cover and well-protected controls all make the saw easy to handle, reduce the risk of getting caught in tree branches and ease transportation.



LowVib reduces fatigue

The handle section is separated from the engine and cutting equipment with steel springs that efficiently reduce tiring vibrations. These durable springs are resistant to fuel, temperature variation and UV light.



Durability

Available with Heavy-Duty air filter.



Air Injection

Centrifugal air cleaning system for longer intervals between filter cleans, smoother operation and reduced wear.

Technical data

Engine

Cylinder displacement	4.48 cu.inch / 73.5 cm ³
Maximum recommended engine speed	13 600 rpm
Fuel tank volume	1.48 US pint / 0.71
Oil tank volume	0.78 US pint / 0.371
Oil pump type	adjustable flow

Cutting equipment

Chain pitch	3/8"
Recommended bar length	16-28" / 40-70 cm

Ergonomics

Sound level	107 dB(A)
Noise emissions, L _{WA}	115 dB(A)
Vibrations, front/rear handle	3.2 m/s ² / 3.4 m/s ²

Overall dimensions

Weight without cutting equipment	14.9 lbs / 6.8 kg
----------------------------------	-------------------

Advantages

- Smart Start decompression valve efficiently reduces the resistance of the starter cord and the new starter handle provides a firm, sturdy grip. A combined choke/stop control allows easier starts and reduces the risk of engine flooding.
- Snap-lock cylinder cover saves time when changing spark plugs and cleaning.
- Side-mounted chain tensioner makes chain adjustment quick and easy.
- Forged three-piece crankshaft for maximum durability for the toughest applications.
- Distinct and coloured felling marks for better felling precision.
- Rubber suspension reduces vibrations in the carburettor, which provides smoother operation and longer product life.
- Accessible, adjustable oil pump with zero flow when idling
- Angled front handle for better grip and natural working position.